


**Disclaimer**  
 The information provided by Delta in this document is for illustration purposes only. Users of this information must not rely on it in any way whatsoever and should confirm information relevant to their needs and specific purpose from other own sources (including with respect to design, specifications, compatibility of products and compliance with rules and regulations). We strongly recommend that you consult relevant experts to assist you with respect to your specific design needs. Delta does not give any guarantees, undertakings or warranties (including implied warranties of merchantability or fitness for a particular purpose) with respect to the information, or any use of the information, including but not limited to:  
 1. the accuracy and completeness of the information or that it is up-to-date.  
 2. the information being fit for any intended or specific purpose;  
 3. the information being compliant with any rules and regulations applicable in the jurisdiction in which the information is supplied.  
 Any party placing reliance on information contained in this document does so at their own risk.  
 In no event shall Delta be liable for any liability (direct or indirect) for any injury, loss, claim, damage or any incidental or consequential damages, including but not limited to lost profits or savings, arising out of or in any way connected with the use of any information, or any error, omission or defect in the information, contained in this document.



**DELTA**  
 DELTA ELECTRONICS AUSTRALIA PTY.LTD.,  
 21/45-57 Normanby Rd, Notting Hill VIC 3168  
 Ph. 1300 335 823

THIS DRAWING IS PROPERTY OF DELTA AND MAY NOT BE COPIED (IN WHOLE OR IN PART) USED FOR MANUFACTURE OR DISCLOSED WITHOUT PRIOR CONSENT OF DELTA PRODUCT CORPORATION. DO NOT SCALE FROM THIS DRAWING

CLIENT:

PROJECT NAME:  
**Winaico PV system designs**

ADDRESS: SCALE:  
 NTS

DRAWING TITLE:  
**PV Electrical Schematic  
 2xH5A-Flex-13 kWp WINAICO 310Wp**

DRAWING NUMBER: SHEET  
**WINAICO-2xH5A-13-A1** 1 of 1

- NOTES:**
- The PV array maximum voltage and Isc shown have been calculated based on an assumed minimum temperature of -5 degrees and the temperature coefficient on the datasheet. These values are temperature dependant and should be calculated for each individual system.
  - The voltage ratings of the DC and ground level DC isolators have been calculated based in the conditions mentioned in note 1 and should be calculated for each individual system. Ensure that DC isolators comply with AS/NZS5033 2014 appendix 5B.
  - DC cabling has been sized based on an installation method of "enclosed touching" and has allowed for a 15m cable run from the roof level DC isolator to the furthest panel. If the actual installation does not meet these requirements, cables should be resized.
  - AC isolators can be omitted if the inverters are located within line of sight and a distance no more than 3m away from the switchboard to which they are connected.
  - The maximum length shown allows for 2% voltage rise between the inverter terminals and the main switchboard, this does not guarantee compliance with all required regulations with regard to voltage rise. The actual location of the point of connection will vary depending the area and supply arrangement. It is the responsibility of the installer to verify compliance of each individual installation with Australian standards, DNSP's and Local Authority Guidelines.
  - The installation method of this cable has been assumed to be "enclosed touching". If actual installation method is different, cable should be resized to suit.
  - Bond earthing to array framing and use Weeb washers between panels and framing. Framing should be bonded so that continuity is maintained even with the removal of a PV module.
  - All work shall be in accordance with AS/NZS3000 2018, AS/NZS3008.1.1 2017, AS/NZS4777.1 2016, AS/NZS4777.2 2015 and AS/NZS5033 2014.
  - Inverters to be export limited to ensure that no more than 5kVA can be exported to the grid. Installer to commission DC1 Data Collector + Inverters to ensure that this is the case. DC1 Data Collector can be powered by a 9-24V DC supply or a 5V micro USB cable.
  - DC1 Data Collector and INV1 + INV2 communicate via radio in order to achieve export control and interlock requirements. If for any reason this radio link is interrupted, INV1 & INV2 will reduce their output to zero in compliance with section AS4777.1 2016 3.4.8.3(c) and the interlock requirement.

**REVISION REGISTER:**

REV	NOTE	DRWN	CHKD	DATE
A1	For Approval	GZ	RM	20/06/19