



EV CHARGING SOLUTION

AC Charger / AC MAX

Features

- 22kW AC charger improves parking turnover
- RFID and ISO 15118 authentication for user management
- Low standby power consumption for energy-saving
- Remote management by built-in network connectivity
- OCPP compliance enables backend system integration
- IP55 and wallmount/stand installation provides high adaptability



Commercial
Building



Parking
Lot



Fleet



Residential
Area



DELTA

Compact and Powerful

AC MAX is a smart AC charger supporting maximum 22kW output and global charging interface. With IP55 / IK10 and compact design, AC MAX provides high adaptability to outdoor and space-limited sites. By supporting ISO 15118, network connectivity and compatible with OCPP, AC MAX reserves the interoperability for system integration and can be an ideal solution for commercial and residential charging sites.



Specifications

Part Number	EVAAE-	
Power	Single Phase	Three Phase
Input / Output Rating	230 Vac, 32 A (maximum), 50 Hz	400 Vac, 32 A (maximum), 50 Hz
Wire	L, N and PE, hardwired with terminal block	L1, L2, L3, N and PE, hardwired with terminal block
Standby Power *	< 2.6 W	
Max. Output Power	7.4 kW	11 kW, 22 kW
Charging Interface *	(1) IEC 62196-2 Type 1 or Type 2 tethered plug, 5 m cable (2) IEC 62196-2 Type 2 Socket (3) IEC 62196-2 Type 2 Socket with shutter	
Protection		
Internal RCD	AC 30 mA, DC 6 mA	
Electrical Protection	Over current, Under voltage, Over voltage, Over temperature, Surge protection, Short circuit, Ground fault	
Upstream Breaker	In accordance with local regulations	
Cold-Load Pickup	Randomized delay before charge resume after power failure	
Automatic Recovery	Automatically resume charging after a minor fault. No user intervention required	
Environment		
Operating Temperature	-30 °C to +50 °C (-22 °F to +122 °F)	
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)	
Humidity	< 95% relative humidity, non-condensing	
Altitude	Up to 4,000m (13,000 ft.)	
Mechanical Design		
Ingress Protection	IP55	
Enclosure Protection	IK10 according to IEC 62262	
Cooling	Natural cooling	
Charging Cable Length	5m	
Dimension (W × H × D)	218 × 371 × 167 mm (8.6 × 14.6 × 6.6 inch) excluding charging cable, mounting plate and cable holder	
Weight	3.8 kg (8.3 lbs), without package	
Regulation		
Certificate / Compliance	CE, IEC 61851-1, IEC 62196-2	
Installation		
Accessory	Stand (optional)	

Delta Electronics (Australia) Pty Ltd

Unit 20-21/45 Normanby Road, Notting Hill, VIC 3168, Australia
TEL: +61-3-9543 3720

For more product information and sales inquiries,
Please contact evcs.service.au@deltaww.com
www.deltaelectronics.com.au

