



Delta DC Wallbox EV Charger

Key Features

- CCS1 or CCS2 / CHAdeMO dual charging ports
- CHAdeMO compliance
- Max. output power: 25kW
- Output voltage range: 200-500Vdc (Combo); 50-500Vdc (CHAdeMO)
- Max. 94% power efficiency
- RFID card reader for user authentication
- Network connectivity (OCPP)
- IP55 protection and IK08 vandal-proof casing

Applications



Highway
Service



Parking



Service
Station



Workplace



Fleet

Power Input	Input Rating	380VAC~415VAC, Three-Phase, 50/60Hz (L1, L2, L3, N, PE)
	Power Factor	> 0.98
	Current THD	Compliant with IEC 61000-3-12 or IEEE 519
	Efficiency	94%
Power Output	DC Output #1	CCS1 or CCS2, 200-500 Vdc, 62 A max., 25kW max.
	DC Output #2	CHAdEMO, 50-500 Vdc, 60A max., 25 kW max.
Protection	Protection	Over current, Under voltage, Over voltage, Residual current, Surge protection, Short circuit, Over temperature, Ground fault
User Interface & Control	Display	2.7" OLED screen
	Support Language	English (Other languages available upon request)
	Push Buttons	Multi-functional buttons (LED light: Orange, Blue) / Emergency stop button (Red)
	Charge Options	Charge by duration, Charge by energy
	User Authentication	ISO/IEC 14443 Type A/B RFID for user authentication
Communication	Network Interface	Ethernet (standard); 3G (optional); Wifi (optional)
Environmental	Operating Temperature	-30 °C to +50 °C (-22 °F to +122 °F)
	Storage Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
	Humidity	< 95% relative humidity, non-condensing
	Altitude	Up to 2000 m. (6500 ft)
Mechanical	Ingress Protection	IP55 or Type 3R
	Enclosure Protection	IK08 according to IEC 62262
	Cooling	Forced air
	Charging Cable Length	4 m (13 ft.)
	Dimension (W x H x D) / Weight	680 x 430 x 230 mm (27 x 17 x 9 in.) 47kg (104 lbs), excluding plug and cable
Regulation	Certificate	UL, cUL, UL 2202, UL 2231
	Compliance	CHAdEMO / IEC 61851-1 / IEC 61851-23, RCM
Compatibility	Compatible vehicle brands	CCS: GM, Ford, BMW; CHAdEMO: Nissan, Toyota, Mitsubishi, Tesla (via adapter)

Specifications are subject to change without prior notice.

Delta Energy Systems (Australia)

Unit 21,
45 Normanby Road
Notting Hill, VIC 3168, Australia.
TEL : +61-3-9543 3720
FAX : +61-3-9544 0606



www.deltaww.com/evcs

LF_EVCS_EVD_EN_V3.0

Delta Electronics, Inc.

3 Dongyuan Road, Zhongli Industrial Zone,
Taoyuan City 32063, Taiwan
TEL : +886-3-4526107
FAX : +886-3-4527314

