

Model	H9E
DC INPUT (SOLAR SIDE)	
Max. input DC power	9280 W
Max. input voltage	600 V
Nominal voltage	380 V
Max. operating voltage	540 V
Start-up voltage	50 V
Operating MPPT voltage range	50 V ~ 480 V
Full power MPPT voltage range	280 V ~ 480 V
Max. input current / MPPT	12 A
Max. short circuit current / MPPT	20 A
Max. DC/AC ratio ¹	1.3
DC disconnect	Integrated
MPP tracker	4
AFCI	Type 1 (UL1699B)
Max. backfeed current to the Array	0 A
AC OUTPUT (GRID-TIED)	
Rated continuous power @ 230Vac	8280 VA
Rated continuous power @ 240Vac	8640 VA
Max. continuous power @ 250Vac	9000 VA
Nominal voltage	230 V / 240 V
Max./rated continuous current	36 A
Max. power export to Grid no CT installed	8280 VA @ 230Vac(adjustable) 9000 VA @ 250Vac (adjustable)
Max. power export to Grid w/ CT installed	5000 VA ²
Max. current export to Grid	21.7 A
Nominal operating frequency	50 Hz
Night consumption	< 1.5 W ³
THD @ rated power	< 3 %
Adjustable power factor range	0.8 ind - 0.8 cap
Inrush current	25.6 Apk, 1ms
Maximum overcurrent protection	45 A
AC OUTPUT (STANDALONE)	
Nominal voltage	230 V / 240 V
Nominal frequency	50 Hz
Rated apparent current	36 A
Rated apparent power	8280 VA
Power factor	0.8 ind - 0.8 cap
BATTERY TERMINAL PARAMETERS	
Nominal voltage	540 V
Range of DC charging voltage	350 V ~ 540 V

Model	H9E
Range of DC discharging voltage	350 V ~ 540 V
Max./Rated charging current	20 A
Max./Rated charging power	6000 W
Max./Rated discharging current	20 A
Max./Rated discharging power	6000 W
Storage type	Lithium
GENERAL SPECIFICATION	
Max. efficiency	98.0 %
EU efficiency	97.3 %
Operating Temp. range	-25 °C to 65 °C (derating above 45 °C)
Storage Temp. range	-40 °C to 85 °C
Humidity	0% to 95%
Max. operating altitude	9,843 ft (3,000 m)
Acoustic noise	< 45 dB(A) @ 3 ft (1m)
Communication interface	WiFi, optional BLE, Ethernet, 3G / 4G cellular communication
Inverter Topology	Non-isolated
Active anti-islanding method	Reactive power variation ⁴ , Comply with IEC 62116
RCMU	Integrated ⁵
Protective class	Class I
Over voltage category	OVC II (PV), OVC III (mains) and OVC II (BAT)
MECHANICAL DESIGN	
Dimensions (W x H x D)	425 x 590 x 168 mm
Display	LED indicators
Weight	21.6 kg
Cooling	Natural convection
STANDARDS	
Enclosure protection rating	IP 65
Safety	IEC 62109-1/-2, IEC 62040
EMC	EN 61000
Grid support regulation	AS/NZS 4777.2:2020
WARRANTY AND OTHERS	
Standard warranty	5 years
Country of manufacturer	Taiwan
Country of production	China

- 1) The DC/AC ratio is defined as the ratio between STC power rating of the connected PV array and rated AC continuous output power @230Vac that can be delivered by a given inverter.
- 2) The export limit of 5KVA is achieved by software if CT is installed.
- 3) Without consumption of WiFi communication
- 4) Periodically inject reactive power variation to grid
- 5) This inverter includes an integrated residual current monitoring unit(RCMU). If an external residual current device (RCD) is used, a device of Type A should be used, with tripping current of 30mA.

Manufacturer Company:

Delta Electronics, Inc.
Address: 3F & 5F No. 16-1, No. 16-1, 2F & 3F & 4F No. 16,
Tungyuan Road, Zhongli District,
Taoyuan City, 320023, Taiwan
E: solarassist@deltaww.com
PH: +886-3-4526107
website: <https://www.deltaww.com/>

Factory Details:

Delta Electronics (Jiangsu) Ltd.
No. 1688, Jiangxing East road, Wujiang Economic and
Technological Development Zone,
Suzhou City, 215200, Jiangsu province, China
E: PCS@deltaww.com
PH: +86 512 6340 1008
Website: <https://www.deltaww.com>

Importer:

Delta Electronics (Australia) Pty Ltd
Unit 18/39
Herbert Street, St Leonards NSW 2065
E: solarassist@deltaww.com
PH: +61-2-9479-4200
website: <http://support.delta-es.com.au/>