

材料安全数据表 Material Safety Data Sheet

样品名称： 储能系统


Sample Name: Energy Storage System

委托单位： 台達電子工業股份有限公司

Applicant: Delta Electronics, Inc.

材料安全数据表 Material Safety Data Sheet

1.化学品及企业标识 Chemical Product and Company Identification	
样品名称 Sample Name	储能系统 Energy Storage System
型号 Model	AIOA279K125L
委托单位地址 Applicant Address	台達電子工業股份有限公司 Delta Electronics, Inc.
委托单位 Applicant	320023 桃園市中壢區東園路 16 號 2 樓 & 3 樓 & 4 樓, 16 號之 1 , 16 號之 1 3 樓 & 5 樓 3F & 5F No. 16-1, No. 16-1, 2F & 3F & 4F No. 16, Tungyuan Road, Zhongli District, Taoyuan City, 320023, Taiwan
生产单位 Manufacturer	中达电子(江苏)有限公司 Delta Electronics (Jiangsu) Ltd.
生产单位地址 Manufacturer Address	江苏省吴江经济技术开发区江兴东路 1688 号 No. 1688, Jiangxing East Road, Wujiang Economic and Technological Development Zone, Suzhou Jiangsu, 215200, China
应急电话 Emergency telephone call	+86-512-63401008
电子邮箱 E-mail	pcs@deltaww.com
邮编 Post Code	215200
澳洲当地服务商 Local Service Provider	DELTA ELECTRONICS (AUSTRALIA) PTY LTD
服务商地址 Service Provider Address	Unit 18/39 Herbert Street, St Leonards NSW 2065 Australia
服务商邮箱 E-mail Address	EngEe.Tan@DeltaWW.com
应急电话 Emergency Contact Number	+61 2 9479 4200
进口商 Importer	DELTA ELECTRONICS (AUSTRALIA) PTY LTD
进口商地址 Importer Address	Unit 18/39 Herbert Street, St Leonards NSW 2065 Australia
进口商邮寄地址 Importer Mailing Address	Unit 18/39 Herbert Street, St Leonards NSW 2065 Australia
进口商邮箱 Importer Email Address	EngEe.Tan@DeltaWW.com
进口商客户支持 Importer Customer Support	+61 2 9479 4200

2.危险性概述 Hazards Identification			
物品危险分类 Hazard label	 No.9A危险性标签 No. 9A hazard label		
爆炸危险性 Explosive risk	该物品不属于爆炸危险品 This article does not belong to the explosion dangerous goods		
易燃危险性 Flammable risk	该物品不属于易燃危险品 This article does not belong to the flammable material		
氧化危险性 Oxidation risk	该物品不属于氧化危险品 This article does not belong to the oxidation of dangerous goods		
毒害危险性 Toxic risk	该物品不属于毒害危险品 This article does not belong to the toxic dangerous goods		
放射危险性 Radioactive risk	该物品不属于放射危险品 This article does not belong to the radiation of dangerous goods		
腐蚀危险性 Mordant risk	该物品不属于腐蚀危险品 This article does not belong to the corrosion of dangerous goods		
其他危险性 other risk	该电池属于锂离子电池 Product belong to the Lithium ion batteries		
3.成分/组成信息 Composition/Information			
成分 Hazardous components	含量 /% Content / wt%	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Graphite	7-25	7782-42-5	231-955-3
Lithium iron Phosphate	15-40	15365-14-7	476-700-9
1,1-Difluoretylen-hexafluorprope npolymer	3-15	9011-17-0	618-470-6
Acetylene black (Carbon black)	0-2	1333-86-4	215-609-9
Copper	10-12	7440-50-8	231-159-6
Aluminum	3-5	7429-90-5	231-072-3
Lithium Hexafluorophosphate	0-5	21324-40-3	244-334-7
Dimethyl Carbonate	0-15	616-38-6	210-478-4
Ethylene Carbonate	0-15	96-49-1	202-510-0

Diethyl Carbonate	0-15	105-58-8	203-311-1
Ethyl Methyl Carbonate	0-15	623-53-0	613-014-2

4.急救措施 First aid measures

眼睛:

万一接触, 立即用大量的清水冲洗至少 15 分钟, 翻起上下眼睑, 直到化学的残留物消失为止, 迅速就医。

Eye

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

皮肤:

万一接触, 用大量水冲洗至少 15 分钟, 同时除去污染的衣物和鞋子, 迅速就医。

Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

吸入:

立即从暴露处移至空气清新处, 如果呼吸困难给予输氧, 立即就医。

Inhalation

Remove from exposure and move to fresh air immediately. Use oxygen if available.

食入:

饮用两杯牛奶或水。如果当事人仍然清晰可以采取催吐的方法, 并且立即就医。

Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician

5. 消防措施 Fire-fighting measures

燃点：不适用

Flash Point: N/A.

自燃温度：不适用

Auto-Ignition Temperature: N/A.

灭火介质：大量水（降温），二氧化碳

Extinguishing Media: Water, CO₂.

特殊灭火程序：自给式呼吸器

Special Fire-Fighting Procedures: Self-contained breathing apparatus.

异常火灾或爆炸：当电芯暴露于过热的环境中时，安全阀可能会打开。

Unusual Fire and Explosion Hazards: Cell may vent when subjected to excessive heat-exposing battery contents.

燃烧产生的危险物品：一氧化碳，二氧化碳，锂氧化物烟气

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

6. 泄露应急处理 Accidental release measures

为防止电池材料泄露或释放采取的措施

如果电池内部材料泄露，试验人员应立即撤离试验区直到烟气消散。将通风设备打开吹散危险性气体。用抹布擦净试验区，清除溢出的液体，将泄露电池放进塑料袋中，然后放进钢制容器。首选的反应是离开该区域，让电池冷却，蒸汽消散，避免皮肤和眼睛接触或吸入蒸汽。

Steps to be Taken in case Material is Released or Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Avoid skin and eye contact or inhalation of vapors.

废弃物处置方法

建议将电池完全放电，消耗电池内部的锂金属，盐水浸泡处理后，交给专业的回收公司处理；或按照当地法规处理。

Waste Disposal Method

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, immerse in salt water, and then give it to a professional recycling company for processing; or handle in accordance with local regulations.

7. 操作处置和储存

Handling and storage

禁止打开、毁坏或焚烧电池，因为电池有可能在这些处理过程中发生爆炸、破裂或泄露等事故。禁止将电池短路、过充、强制放电或扔入火中。禁止挤压刺穿电池或将电池浸入溶液中。

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

操作处置和储存中的防范措施

禁止物理或电滥用，禁止高温储存，最好将电池储存在阴凉、干燥、通风等温度变化较小的环境中。禁止将电池接触加热设备或将电池直接暴露与阳光中。

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

其他要注意的防范措施

拆解、挤压、直接放入火中或高温条件下，电池可能发生爆炸和燃烧。禁止短接或将电池正负极错误的安装在设备中。

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. 接触控制/个人防护

Exposure controls/personal protection

呼吸防护：

当电池排气阀打开时，应尽量使通风设备开至最大，避免将打开排气阀的电芯局限在某一狭窄空间内。正常操作条件下，呼吸保护是不必要的。

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores.

Respiratory Protection is not necessary under conditions of normal use.

通风条件

正常使用条件下不需要。

Ventilation

Not necessary under conditions of normal use.

防护手套

正常使用条件下不需要。

Protective Gloves

Not necessary under conditions of normal use.

其他防护服装或设备

正常使用条件下不需要。

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

电池开阀试验时应做好个人防护

呼吸防护，防护手套，防护服装和有护边的安全玻璃罩都是要准备的。

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

9. 物理和化学特性

Physical and chemical properties

外形：长方形

Appearance: Cuboid

气味：泄漏时，有醚的气味。

Odors: If leaking, smells of medical ether.

酸碱度：不适用

pH: Not applicable as supplied.

燃点：除单个电芯暴露试验外其他不适用。

Flash Point: Not applicable unless individual components exposed.

可燃性：除单个电芯暴露试验外其他不适用。

Flammability: Not applicable unless individual components exposed.

相对密度：除单个电芯暴露试验外其他不适用。

Relative density: Not applicable unless individual components exposed.

溶解性（水溶性）：除单个电芯暴露试验外其他不适用。

Solubility (water): Not applicable unless individual components exposed.

溶解性（其他）：除单个电芯暴露试验外其他不适用。

Solubility (other): Not applicable unless individual components exposed.

10. 稳定性和反应活性

Stability and reactivity

稳定性：产品在第7节所述的条件下稳定。

Stability: Product is stable under conditions described in Section 7.

应避免的条件：加热70°C以上或焚烧。变形。毁坏。粉碎。拆卸。过充电。短路。长时间暴露在潮湿的条件下

Conditions to Avoid: Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.

应避免的材料：氧化剂，碱，水。

Materials to avoid: Oxidising agents, alkalis, water.

危险分解物：有毒烟雾，并可能形成过氧化物。

Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.

聚合危害：不适用

Hazardous Polymerization: N/A.

如果发生泄露，避免与强氧化剂，无机酸，强碱，卤代烃接触。

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated Hydrocarbons.

11. 毒理学资料 Toxicological information

标志及症状：无，除非电池破裂。

Signs & symptoms: None, unless battery ruptures.

内部物质暴露的情况下，蒸汽烟雾可能对眼睛和皮肤的刺激性。

In the event of exposure to internal contents, vapor fumes may be very irritating to the eyes and skin.

吸入：对肺有刺激性。

Inhalation: Lung irritant.

皮肤接触：对皮肤刺激性。

Skin contact: Skin irritant.

眼睛接触：对眼睛有刺激性。

Eye contact: Eye irritant

食入：吞下中毒。

Ingestion: Poisoning if swallowed.

下列情况下健康状况会恶化：万一发生与电池内部材料接触的事故，轻微或严重的刺激，都可能使皮肤出现干燥和灼烧的感觉，并且损坏靶器官（肝脏，肾脏）的神经。

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to severe irritation, burning and dryness of the skin may occur, Target Organs nerves, liver and kidneys.

12. 生态学资料 Ecological information

对哺乳动物的影响：目前未知。

Mammalian effects: None known at present.

生态毒性：目前未知。

Eco-toxicity: None known at present.

生物体内积累：慢慢地生物降解。

Bioaccumulation potential: Slowly Bio-degradable.

环境危害：目前没有已知的环境危害。

Environmental fate: None known environmental hazards at present.

13. 废弃处置 Disposal consideration

不要焚烧，或使电池温度超过70°C，这种滥用可导致泄漏和/或电池爆炸。按照相应的地方性法规处理。

Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

14. 运输信息 Transport information

运输标签: No.9A危险性标签
Label for conveyance: No.9A hazard label hazard label
UN编号: UN 3480
UN Number: UN 3480
运输专用名称: 锂离子电池
Proper Shipping name: Lithium ion batteries
IMDG Code/TDG包装导则: P903(2)
IMDG Code/TDG Packing Instruction: P903(2)
IMDG Code/TDG 特殊规定: 230, 310, 348, 376, 377, 384, 387
IMDG Code/TDG Special provisions: 230, 310, 348, 376, 377, 384, 387
EmS编号: F-A, S-I
EmS No: F-A, S-I
海洋污染物: 无
Marine pollutant: No
危害分类: 货物应遵守联合国关于危险货物运输的建议书规章范本第二十三版和IMDG Code (Amdt.42-24) 包装导则P903(2)的要求。包括通过UN38.3测试手册要求。
Hazard Classification: The goods shall be complied with the Packing Instructions TDG 23th Edition and the Packing Instructions P903(2) of IMDG Code (Amdt.42-24), including the passing of the UN38.3 test.

15. 法规信息 Regulation information

主要可适用锂电池运输的法律法规如下:
The laws and regulations applicable to the transportation of lithium batteries are as follows:
联合国《关于危险货物运输的建议书 规章范本》ST/SG/AC.10/1/Rev 23.
The UN Model Regulations, United Nations ST/SG/AC.10/1/Rev 23. Recommendations on the Safe Transport of Dangerous Goods
国际民用航空组织 (ICAO) 技术指令对于通过航空对危险货物的安全运输要求
The International Civil Aviation Organization (ICAO) Technical Instructions for the Safe Transport of Dangerous Goods by Air Transport
国际航空运输协会 (IATA) 危险货物运输规则 (2025 版 66th)
The International Air Transport Association (IATA) Dangerous Goods Regulations (66th Edition 2025)
国际海事协会 (IMO) 国际海事危险货物规则(IMDG Code) (Amdt.42-24)
International Maritime Organization (IMO) International Maritime Dangerous Goods Code (IMDG Code)(Amdt.42-24)
《危险品公路运输欧洲协议》 (2025年版)
Agreement concerning the International Carriage of Dangerous Goods by Road (ADR 2025)
JT/T 617-2018 《危险货物道路运输规则》
JT/T 617-2018 Regulations concerning road transportation of dangerous goods

16. 其他信息 Other information

本文件仅对由委托方提供的，并由中达电子(江苏)有限公司的电柜（型号：AIOA279K125L）有效。该电池的成分信息由委托方提供并承诺其完整性和准确性。

用户应仔细阅读此文件，并按照正确的方法使用电池，如因电池使用不当造成的损害或损失，广州海关技术中心（IQTC）不承担任何责任。

This file is only effective to the Rack (Model: AIOA279K125L) provided by commissioner which manufactured by Delta Electronics (Jiangsu) Ltd. The commissioner provides the composition information of batteries, and promises its integrity and accuracy.

Users should read this file carefully, and use the batteries in correct method. GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER doesn't assume responsibility for any damage or loss because of misuse of batteries.

* * * * 报告结束 End of report * * * *